TECHNICAL DATA SHEET

Issue date: 01/02/2026

Cod. 1070
Flexible handle in acetal resin

Flexible handle with stainless steel ends, to be used with interchangeable tube brushes.

Certifications and regulatory compliance

- Regulation (EC) No 1907/2006 (REACH) and updates

Conditions of use and safety requirements[1]	
Operating temperature	min -20 / max 80 C°
Dishwasher resistance[2]	Tested at 65°C according to BS EN 12875-1:2005
Steam sterilization	Compatible with autoclave cycles at 121°C for 15 minutes according to ISO 17665-1:2006
Instructions for use	• Remove all packaging and/or labels. • Sanitize/disinfect according to HACCP protocol. • Hang the tool using appropriate hooks/supports. • Allow to dry completely before use.
Signs of deterioration	The product must be regularly inspected. Observable signs of deterioration include: • Material softening, breakage, or discoloration; • Detachment of parts or structural damage. If any such issues are detected, the product must be withdrawn from food contact use and replaced, as also required under Regulation (EU) 2023/988 on general product safety.

Technical specifications			
Length (mm)	850	Material	POM
Width (mm)	-	Net weight (kg)	0,06
Height (mm)	-	Quantity per pack (pcs)	6
Diameter (mm)	9		

[1] in accordance with Regulations (EU) 2025/351 and 2023/988

[2] Exposure to high temperatures or intensive cycles may cause bristle deformation or material degradation.

IGEAX S.R.L. - Via delle Querce 16 - Z.I. Fenilrosso - 46019, Viadana (MN) - ITALY - Tel.: +39 0375 780798 - Mail: info@igeax.com